

LUCIDA[®]

SURFACES

setting life's stage[™]



DecoCORE[™]



A stage is as sound as its foundation, as strong as its core and as stylish as its surface.

EnCore™

EnCore™ Technology is a bespoke surface because a symphony is as memorable as its finish.

Urethane with Ceramic Bead Finish



4x UV coat plus ceramic bead finish for super-max strength and quality.

Abrasion and Stain Resistant



22 MIL hardened vinyl wear layer provides excellent resistance to abrasive scuffs and stains.

HD Decorative Film



High definition film prints create vivid, natural hardwood look.

Heavy Duty



For residential, commercial and light Industrial.

Density: 3000kg/m³

CorePrit™

CorePrit™ Technology is a white limestone core essence that is the spine of our product

100% Virgin Premium SPC (Stone Polyvinyl Composite)



100% phthalate-free extruded closed-cell core provides exceptional rigidity, dimensional stability, and anti-telegraphing performance.

Advanced Unilin® Locking System



The industry's strongest and most innovative drop and lock system enables quick, easy, hassle-free installation.

Micro-Bevel Edges.

CoreTech™

CoreTech™ Technology is a subtle, adhering material that grounds every plank.

IXPE Quiet integrated sound reduction underlayment



Bonded cross-linked underlayment minimizes impact and transmitted sound, provides underfoot warmth and comfort, and mitigates subfloor imperfections. (IIC 72 Db, STC 71 Db) Anti-microbial.



100% Waterproof
Rigid Core Performance



25 Year Warranty
10 Years Commercial



5.05"
Width 128.27 mm



31"
Length 787.4 mm



0.27"
Thickness 7 mm



22 mil
Wear Layer .55 mm



Woodgrain Texture



Unilin® Locking System

DecoCORE™

Building on the industry-leading MaxCore™ 3rd gen. platform, DecoCore™ is a thicker, smaller plank and comes in 'right' and 'left' planks to allow for Herringbone designs.

Wear Layer

1. Urethane with Ceramic Bead Finish
2. 4x UV coat for super-max strength and quality.
3. Wear Layer provides resistance to abrasive scuffs and stains.

Core

- HD Decorative Film for vivid, natural look
- 100% Virgin Premium SPC Core with advanced Unilin® Locking System
- IXPE Quiet integrated sound reduction underlayment



Box

16
planks

17.5
sq ft

Pallet

49
boxes

857.5
sq ft



CERTIFIED BY
SCS Global Services

The Jazz Collection

A little edgy, a little groovy, The Jazz Collection goes against the grain. A wide-range of on- and offbeat patterns allows mixing and matching in bluesy rhythm.

Pattern Options

Herringbone
Pattern: Uses A+B planks



Straight
Pattern: Uses A or B planks



701 | White Oak



Art deco, artful, decorative, the Jazz Age



702 | Peak Shine



The tune is familiar, the rhythm is unexpected



703 | Soft Gray



Like a business casual suit, perfect for weekend meetings

ITEM	SPECIFICATION
------	---------------

TECHNICAL SPECIFICATIONS

Dimensions	Width: 5.05" (128mm) Length: 31" (787mm)
Thickness	Overall: 0.27" (7mm) Wear Layer: 0.55 mm (22mil)
Profile	Micro-Bevel Edges
Coverage	17.5 sq.ft (1.63 sq.m) /box, 857.5 sq. ft (79.6 sq.m) /pallet
Planks per Carton	16 Planks
Cartons per Pallet	49 boxes
Weight	36.2 lbs. (16.4 kg) /box, 1,788 lbs. (811 kg) /pallet
Composition	100% Virgin Premium SPC (Stone Polyvinyl Composite)
Type	Floating-floor with easy-install industry-leading UNilin™ Locking System
Application	Residential & Commercial
Surface Treatment	4x UV Coating, Anti-Microbial Embedded with Ceramic bead Finish
Visual Pattern Repeat	Approx. every 1,200mm (39.37in)
Print pattern repeat	Approx. 1 plank in every 10 cartons
Backing	Moisture Resistant
Warranty	10 Year Limited Commercial 25 Year Limited Residential

PERFORMANCE

Classification	EN ISO 10582 Domestic Commercial Light Industrial	Heavy Class 23 Very Heavy Class 34 Heavy Class 43	Slip Resistance — Wet	Din 51130	Surpasses
Size & Straightness	EN 426	Passes	Chemical Resistance	EN 423	No Effect
Thickness	EN 428	Passes	Reaction To Fire	EN 13501-1	Bfl-S1 Classification
Dimensional Stability	EN 434	Surpasses	100% Phthalate Free		Yes
Flexibility	EN 435	Passes	100% Waterproof		Yes
Residual Stability	EN 433	Surpasses	Antimicrobial		Yes
Castor Chair	ISO 4918	Passes	Environmental Certification		Floorscore Certified
Color Fastness To Light	ISO 105-B02	Surpasses	Scratch/Abrasion		Excellent
Product-Content Safety	Reach Svhc 163	Passes	Slip Resistance		Class Ds
Formaldehyde Emission	EN 717-1	0 Mg/M	lic (Impact Isolaton Class)	Impact Sound Absorption 72 Db	
Slip Resistance — Dry	EN 13893	Surpasses	STC (Sound Transmission Class) Traveling Sound Absorption	71 Db	
			Use With Radiant Flooring		Recommended



LUCIDA®
SURFACES
setting life's stage™

Lucida Surfaces USA

P.O. Box 327, Tallman, NY 10982

Warehouse:

525A South Avenue,
Plainfield, NJ 07060
+1 (845) 877-7008

Lucida Surfaces Canada

8620 Rue Pascal-Gagnon
Montreal QC H1P 1Z1
+ (514) 587-9926

LiveOnLucida.com