

LUCIDA[®]

SURFACES

setting life's stage[™]



MaxCORE[™]



This: 501 Jasper | Cover: 502 Carnelian

A stage is as sound as its foundation, as strong as its core and as stylish as its surface.

EnCore™

EnCore™ Technology is a bespoke surface because a symphony is as memorable as its finish.

Urethane with Ceramic Bead Finish



4x UV coat plus ceramic bead finish for super-max strength and quality.

Abrasion and Stain Resistant



22 MIL hardened vinyl wear layer provides excellent resistance to abrasive scuffs and stains.

HD Decorative Film



High definition film prints create vivid, natural hardwood look.

Heavy Duty



For residential, commercial and light Industrial.

Density: 3000kg/m³

CorePrit™

CorePrit™ Technology is a white limestone core essence that is the spine of our product

100% Virgin Premium SPC (Stone Polyvinyl Composite)



100% phthalate-free extruded closed-cell core provides exceptional rigidity, dimensional stability, and anti-telegraphing performance.

Advaced Unilin® Locking System



The industry's strongest and most innovative drop and lock system enables quick, easy, hassle-free installation. Micro-Bevel Edges.

CoreTech™

CoreTech™ Technology is a subtle, adhering material that grounds every plank.

IXPE Quiet integrated sound reduction underlayment



Bonded cross-linked underlayment minimizes impact and transmitted sound, provides underfoot warmth and comfort, and mitigates subfloor imperfections. (IIC 72 Db, STC 71 Db) Anti-microbial.



100%
Waterproof
Rigid Core Performance



25 Year
Warranty
10 Years Commercial



7 5/16"
Width 185 mm



48"
Length 1220 mm



0.22"
Thickness 5.5 mm



22 mil
Wear Layer .55 mm



Woodgrain
Texture



Unilin®
Locking System

MaxCORE

The MaxCore™ 3rd gen. waterproof flooring system has the highest industry components, technologies and ratings. Available in Classic and modern looks and textures.

Wear Layer

1. Urethane with Ceramic Bead Finish
2. 4x UV coat for super-max strength and quality.
3. Wear Layer provides resistance to abrasive scuffs and stains.

Core

- HD Decorative Film for vivid, natural look
- 100% Virgin Premium SPC Core with advanced Unilin® Locking System
- IXPE Quiet integrated sound reduction underlayment



Box

10
planks

24.5
sq ft

Pallet

45
boxes

1102.5
sq ft



The Classical Collection

Playing off the timeless hues and natural grains of classic wood floors, The Classical Collection is a symphony of elegant beauty.



501 | Jasper



Warm and inviting, like hot cocoa on a winter morning



504 | Carnelian



Smooth and comforting, urban farmhouse



505 | Hesonite



Dancefloor for the rhythm of everyday

The Classical Collection

Playing off the timeless hues and natural grains of classic wood floors, The Classical Collection is a symphony of elegant beauty.



508 | Siliceous



Lending a natural, organic ambiance



509 | American Oak



As if a rich cello were underfoot



511 | Pioneer Oak



Classic lines, shellacked perfection

The Pop Collection

Cutting edge and modern chic, the popular color tones of The Pop Collection are curated from the industry's top-selling styles, so you don't have to sift through endless options.



502 | Obsidian



Cool, hip, urban professional, a lawyer who wears jeans



503 | Silver Leaf



Classy, modern, clean, who everyone wants to be



506 | Dolomite



Elegance with an edge, like a gravelly smooth radio voice

The Pop Collection

Cutting edge and modern chic, the popular color tones of The Pop Collection are curated from the industry's top-selling styles, so you don't have to sift through endless options.



507 | Andesite



Calculated and mathematical, you can hear the room click




510 | Storm Black



A cup of coffee, brewed with extravagant beans



512 | Piano White



513 | Piano Black

ITEM	SPECIFICATION	
TECHNICAL SPECIFICATIONS		
Dimensions	Width: 7.28" (185 mm), Length: 48" (1,219 mm)	
Thickness	Overall: 0.22" (5.5mm) Wear Layer: 0.55 mm (22mil)	
Profile	Micro-Bevel Edges	
Coverage	24.5 sq.ft (2.28 sq.m) per box, 1102.5 sq.ft (102.4 sq.m) per pallet	
Planks per Box	10 Planks	
Boxes per Pallet	45 Boxes	
Weight	41 Lbs. (18.6 kg) per box, 1,837 lbs. (8,969 kg) per pallet	
Composition	100% Virgin Premium SPC (Stone Polyvinyl Composite)	
Type	Floating-floor with easy-install industry-leading UNilin™ Locking System	
Application	Residential & Commercial	
Surface Treatment	4x UV Coating, anti-microbial embedded with Ceramic bead Finish	
Visual Pattern Repeat	Approx. every 1,200mm (39.37in)	
Print pattern repeat	Approx. 1 plank in every 10 boxes	
Backing	IXPE Moisture Resistant, Sound Reducing material	
Warranty	10 Year Limited Commercial	25 Year Limited Residential

PERFORMANCE

Classification	EN ISO 10582 Domestic Commercial Light Industrial	Heavy Class 23 Very Heavy Class 34 Heavy Class 43	Slip Resistance — Wet	Din 51130	Surpasses
Size & Straightness	EN 426	Passes	Chemical Resistance	EN 423	No Effect
Thickness	EN 428	Passes	Reaction To Fire	EN 13501-1	Bfl-S1 Classification
Dimensional Stability	EN 434	Surpasses	100% Phthalate Free		Yes
Flexibility	EN 435	Passes	100% Waterproof		Yes
Residual Stability	EN 433	Surpasses	Antimicrobial		Yes
Castor Chair	ISO 4918	Passes	Environmental Certification		Floorscore Certified
Color Fastness To Light	ISO 105-B02	Surpasses	Scratch/Abrasion		Excellent
Product-Content Safety	Reach Svhc 163	Passes	Slip Resistance		Class Ds
Formaldehyde Emission	EN 717-1	0 Mg/M	Iic (Impact Isolation Class)	Impact Sound Absorption 72 Db	
Slip Resistance — Dry	EN 13893	Surpasses	STC (Sound Transmission Class) Traveling Sound Absorption	71 Db	
			Use With Radiant Flooring		Recommended



LUCIDA®
SURFACES
setting life's stage™

Lucida Surfaces USA

P.O. Box 327, Tallman, NY 10982

Warehouse:

525A South Avenue,
Plainfield, NJ 07060
+1 (845) 877-7008

Lucida Surfaces Canada

8620 Rue Pascal-Gagnon
Montreal QC H1P 1Z1
+ (514) 587-9926

LiveOnLucida.com