

US Vinyl Wallcovering

- **USV manufacturing procedures support and protect the environment**
- Contains pre-consumer and post-consumer recycled content
- **All inks and adhesives are water based and eco-friendly**
- All unused inks are recycled
- All outbound and incoming packaging is 100% recycled content
- **During manufacture, trimming and waste products are recycled**
- Utilization of closed loop water system
- **100% recyclable** - resulting in a virtually endless life cycle.
- All wallcoverings are produced with **low VOC** substrate



USV WALLCOVERING

US Vinyl is one of the top commercial wall covering manufacturers within the world-wide wallcovering industry.

Manufactured in Lafayette, Georgia.

Known for their superior design and unbeatable pricing, USV continues to grow and meet the industry's needs.

SPECIFICATIONS

Technical Information

USV Wallcovering Specifications

UNIT OF MEASURE

Patterns are available 54" wide, sold by the linear yard.

- linear yard is 54" x 36" = 13.5 SF

PACKAGING

- 54" wide goods are packaged in 50 yard bolts.
- A cut charge of \$1.50/LY applies to orders other than 50 LY increments.

TECHNICAL DATA

Wallcoverings meet all federal specifications for CCC-W408-A & B, Type I and Type II.
Flame spread rating is Class A.

	Type I Results		Type II Results		
Ounce Weight	12/13oz.	15/16oz.	18/19oz.	20/21oz.	24oz.
Flame Spread	5	10	5	10	10
Smoke Developed	0	0	0	0	20

All patterns are tested per ASTM-E-84 CLASS A by an independent research laboratory.
Test results are available upon request.

SPECIFIED

SOLUTIONS

Commercial Floors & Walls